

Vaseline Oil

The agent used to lubricate machine parts and precision mechanisms. Non-staining, odourless, colourless, neutral in contact with plastics. Reduces friction, preserves elements exposed to weather conditions, and protects against the adherences of plastic or rubber products to the mould. Consistency of the preparation allows for a wide range of applications.

Physicochemical properties		
Product form	aerosol	fluid
Appearance	colorless gas	transparent
Density at 20 °C	0,85 - 0,88 g/cm ³	
Kinematic viscosity at 40 °C	66-74 mm ² /s	
Operating temperature	-10 °C to 90 °C	

Application:

- the preparation reduces and limits friction,
- ideal for lubricating machinery and equipment, as well as any precision mechanisms,
- the oil effectively eliminates squeaks and scuffs, facilitates slipping,
- protects and preserves rubber and plastics.

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
50 ml	plastic bottle with applicator	12	ART.AGT-017
100 ml	plastic bottle with applicator	12	ART.AGT-018
300 ml	aerosol	12	ART.AGT-019
1 L	plastic bottle	1	ART.AGT-099
5 L	plastic canister	1	ART.AGT-245

Warehousing:

Store in tightly closed containers in a cool and dry place, away from heat sources and direct sunlight. Store at a temperature of 0-50 °C. Do not store together with oxidising substances. Do not apply PVC packages.